



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



GM8

AUTOMATIC GROUT MIXER PLANT



Skid frame dimensions and weight

| | | |
|--------|---------|---------|
| Width | 1340 mm | 4'5" |
| Lenght | 1950 mm | 6'5" |
| Height | 1770 mm | 5'9" |
| Weight | 1000 Kg | 2204 lb |



Technical Features

| | | | |
|---|------------------------|-------------------|----------------|
| Electronic load cell weighing system / système de pesage électronique/ Wägeelektronik für Wägezellen | | | |
| Max hourly capacity / capacité horaire maximum / maximale Stundenleistung | 8 m³ | 35 gpm | |
| Electric power consumption / consommation électrique / Stromverbrauch | 8 kW | | |
| MIXER | | | |
| Max capacity / capacité maximale / maximale Kapazität | 200 lt | 53 gal | |
| OPTIONAL HIGH CAPACITY MIXER | 300 lt | 80 gal | |
| Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate | @1 bar | 750 lt/min | 198 gpm |
| Pump motor / moteur de pompe / Pumpenmotor | 5,5 kW | | |
| AGITATOR | | | |
| Max capacity / capacité maximale / maximale Kapazität | 500 lt | 132 gal | |
| OPTIONAL HIGH CAPACITY AGITATOR | 700 lt | 185 gal | |
| Electric motor / moteur électrique / elektromotor | 0,75 Kw | | |
| AIR COMPRESSOR | | | |
| Air compressor capacity / capacité du compresseur d'air/ Luftverdichter Kapazität | 400 lt/min | 105 gpm | |
| Air tank / réservoir d'air / luftbehälter | 100 lt | 26,4 gal | |
| Electric motor / moteur électrique / elektromotor | 3 kW | | |



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice