



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TW Silo 30T

HORIZONTAL STACKABLE SILO



Technical Features

Remote control panel from mixing plant / panneau de commande à distance de l'usine de mélange / *Ernbedienfeld von Mischanlage*

Manual or automatic control / contrôle manuel ou automatique / *manuelle oder automatische Steuerung*

Timed working / travail temporisé / *arbeiten Seitgesteuertes*

Self-supporting steel frame / structure autoportante en acier / *selbsttragende Stahlkonstruktion*

CSC CERTIFICATE

Water filter / filtre à eau / *Wasserfilter*

Pressure safety valve / soupape de sûreté de pression / *Drucksicherheitsventil*

Tool box / boîte à outils / *Werkzeugkasten*

Twist lock kit

Set for «Safety Kit» / fixé pour «Safety Kit» / *vorbereitet für «Safety Kit»*

TOTAL CAPACITY

Max capacity / capacité maximale / *maximale Kapazität*

30 ton

66.138 lb

Max load volume / volume de chargement maximum / *maximales Ladevolumen*

22.7 m3

801 cu ft

Screw conveyor capacity / Capacité de convoyeur à vis / *Förderschnecken Kapazität*

40 ton/h

88.185 lb/h

Electric motor / moteur électrique / *Elektromotor*

9,2 kW

Electric vibrators / vibrateurs électriques / *elektrische Vibratoren*

N°6

UPGRADE 30T+30T

Preset to join with additional upper silo / prêt être conjoint avec silo supérieur supplémentaire / *Vorbereitet für höher Silo*

Dimensions and weight

Width 2438 mm - 7'12"

Lenght 6055 mm - 19'1"

Height 2896 mm - 9'6"

Weight 7500 - 16535 lb



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecnowell.com – www.tecnowell.it

All technical data are purely indicative and subject to change without notice