






TW 351 CU CEMENTING UNIT TRUCK MOUNTED



Technical specifications

PUMP TW351	 n. 3 single acting plungers pump stroke plunger size max. working SPM suction dia. delivery dia. 		p for very h 5" 3 1/2" 100 4" 1" 1/2	igh pressure (127,0 mm) (88,9 mm) (101,6 mm) (38,1 mm)	
PERFORMANCE (With 3 1/2" plunger)	max intermittent pressure max continuous pressure max working delivery max peak delivery		500 bc 235 lt/	550 bar 500 bar 235 lt/min 310 lt/min	
WATER TANK	4000 lt capacity				
MIXING TANK	500 lt capacity with impeller hydraulic driven				
AUXILIARY PUMP	900 lt/min hydraulic driven				
DIESEL ENGINE (Standard)	Make Model N° cylinders Power	Model DC 9 N° cylinders 6 Turbo intercooler			
GEAR BOX	ZF, with remote control pneumatic operated and oil forced lubrication by oil gear pump				
TRUCK	MOD. ASTRA HD7 64.38 6x4 – Power 370 HP Engine IVECO – 6 CYLINDERS – Turbo intercooler Gear Box ZF				



Tecniwell S.r.l. - Via I° Maggio, 61 - 29027 Podenzano (PC) Italy T +39 0523 524086 - F +39 0523 524088 E mail:info@tecniwell.com - http://www.tecniwell.com