




JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



# TW 800

HIGH PRESSURE TRIPLEX PUMP



## Technical Features

<b>Max power input / puissance max / maximale Kraft</b>	<b>566 kW</b>	<b>770 HP</b>
<b>Max pressure / pression maximale / maximaler Druck</b>	<b>82 MPa</b>	<b>820 bar</b>   <b>11890 psi</b>
<b>Max flow rate / débit maximale / maximale Durchflussrate</b>	<b>2500 lt/min</b>	<b>660 gpm</b>
<b>Piston diameter / diamètre du piston / kolbendurchmesser</b>	From 4" (101,6mm) to 7"1/2 (190,5mm)	
<b>Stroke / Course / Hubweg</b>	8" – 177,8	
<b>Maximum stroke rate / coup par minute / max Hub pro Minute</b>	140 / min	140 spm
<b>Suction diameter / diamètre d'aspiration / Saugdurchmesser</b>	8"	203,2 mm
<b>Output diameter / diamètre de sortie / Ausgangsdurchmesser</b>	3"	76,2 mm


7" Control panel lcd monitor

### Bareshaft dimensions and weight

Width 1600 mm - 5'3"	Height 1030 mm - 3'5"	Lenght 2450 mm - 8'	Weight 7500 Kg - 16534 lb
----------------------	-----------------------	---------------------	---------------------------

### Container dimensions and weight

Width 2500 mm - 8'2"	Lenght 7103 mm - 23'4"	Height 2870 mm - 9'5"	Weight 18000 Kg - 39683 lb
----------------------	------------------------	-----------------------	----------------------------



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086  
e-mail: [info@tecniwell.com](mailto:info@tecniwell.com) – [www.tecniwell.it](http://www.tecniwell.it)

All technical data are purely indicative and subject to change without notice