



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



GMP59D

DIESEL MANUAL GROUT MIXING / INJECTION UNIT

Overall dimensions and weight

WIDTH	LENGHT	HEIGHT	WEIGHT
2050 mm - 6'8"	3420 mm - 1'2"	2200 mm - 7'2"	2900 kg - 6393 lb



MIXER TECHNICAL FEATURES


Max hourly capacity / capacité horaire maximum / maximale Stundenleistung	5 m³	22 gpm	
Diesel power / puissance du diesel / Dieselkraft	25 kW		
MIXER			
Max capacity / capacité maximale / maximale Kapazität	200 lt	53 gal	
Max pump flow rate / pompe débit maximale / Pumpe maximale Surchflussrate	@1 bar	750 lt/min	198 gpm
AGITATOR			
Max capacity / capacité maximale / maximale Kapazität	500 lt	132 gal	

PUMP TECHNICAL FEATURES

Double effect piston / piston à double effet / Doppeleffekt Kolben			
Max flow rate / débit maximale / maximale Durchflussrate	150 lt/min	40 gpm	
Max pressure rate / pression maximale / maximal Druckrate	90 bar	9 MPa	1305 PSI
Piston diameter / diamètre du piston / Kolbendurchmesser	5"	127 mm	
Stroke / course / Hubweg	8'	203 mm	
Max stroke rate / coup par minute / max Hub pro Minute	32 / min	32 spm	
Suction diameter / diamètre d'aspiration / Saugdurchmesser	3"	76,2 mm	
Output diameter / diamètre de sortie / Ausgangsdurchmesser	1"1/4	31,75 mm	

DIAGRAMMA PORTATA - PRESSIONE
PRESSURE-FLOW RATE DIAGRAM

PORTATA - FLOW RATE
(gpm)



tw tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice