



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TW Silo 50T

HORIZONTAL STACKABLE SILO



Technical Features

Remote control panel from mixing plant / panneau de commande à distance de l'usine de mélange / *Ernbedienfeld von Mischanlage*

Manual or automatic control / contrôle manuel ou automatique / *manuelle oder automatische Steuerung*

Timed working / travail temporisé / *arbeiten Seitgesteuertes*

Water filter / filtre à eau / *Wasserfilter*

Pressure safety valve / soupape de sûreté de pression / *Drucksicherheitsventil*

Tool box / boîte à outils / *Werkzeugkasten*

Twist lock kit

TOTAL CAPACITY

Max capacity / capacité maximale / *maximale Kapazität*

50 ton

110231 lb

Max load volume / volume de chargement maximum / *maximales Ladevolumen*

37 m3

1307 cu ft

Screw conveyor capacity / Capacité de convoyeur à vis / *Förderschnecken Kapazität*

32 ton/h

70547 lb/h

Electric motor / moteur électrique / *Elektromotor*

9,2 kW

Electric vibrators / vibrateurs électriques / *elektrische Vibratoren*

N°4

Dimensions and weight

Width 2500 mm - 8'2"

Lenght 8500 mm - 27'10"

Height 3000 mm - 9'10"

Weight 6000 - 13227 lb

tw tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice